

RF-4041-07-2

2-way key fob LoNa



OVERVIEW

This 4-button 2-way keyfob, using the latest LoNa technology, allows the end-user to arm, disarm or partially arm their system without having to memorise access codes or race to beat entry or exit delays.

Each button press will be indicated by a blinking LED and the acknowledgement coming from the receiver will also trigger the LED on the keyfob.

In case the system is not ready to arm, or in case the end-user is out of range of the receiver, this will also be visible on the keyfob when pressing a button. Even a system in alarm, will be indicated when performing a button press.

It offers one additional programmable buttons which can be used e.g. to turn on and off lights before entering the premises, activate an automated garage door, etc.

It can also be used to send a panic alarm by pressing the lock and unlock buttons simultaneously, or to trigger an auxiliary alarm by pressing the "1" and "2" button simultaneously.

FEATURES

- Using LoNa technology
- Compact, robust, premium design
- LED confirmation of sent and received messages
- Out-of-range LED indication
- 1 programmable button
- Panic and Auxiliary alarm functionality available
- 5 years of battery life (based on usage)

RF-4041-07-2

2-way key fob LoNa

National Sales Enquiries
Level 4.01, 2 Ferntree Place
Notting Hill, Victoria 3168
Phone: 1300 361 479
Outside Australia: +61 401 777 572
www.aritech.com.au

TECHNICAL SPECIFICATIONS

General

Accessory group	Key Fob
Type	Credential

Electrical

Wireless operating frequency	433.65 MHz
Wireless power output	-9 dBm EIRP
Battery type / life	3 V lithium CR2032 / 5 years
Wireless operating frequency	433.65 MHz
Wireless power output	-9 dBm EIRP
Battery type / life	3 V lithium CR2032 / 5 years

Physical

Physical dimensions	32 x 13 x 63 mm
Net weight	42.5 g

Environmental

Operating temperature	0° to 49°C
Relative humidity	5 to 95% noncondensing

Regulatory

Compliance	CE, RCM
------------	---------